

# AQ02F

## LIFEJACKET LIGHT

The AQ02F has been designed for use with foam lifejackets. Once the holder has been inserted into the lifejacket the AQ02F can be fitted. This feature not only makes the light less vulnerable to tampering, but also greatly reduces the risk of damage when used in conjunction with evacuation systems. Its unique activation switch offers the user a choice of either manual or automatic operation.

### TECHNICAL SPECIFICATIONS

Activation	Man On / Auto On / Man Off
Dimensions	80mm(h) x 30mm(w) x 30mm(d)
Output	0.75cd
Duration	Min 8hrs
Shelf Life	5 Years

0086/02  
MED 2002/75/EC, IMO MSC 81 (70)

# AQ180

## LIFEBUOY LIGHT

The AQ180 is a self-activating lifebuoy light conforming to the latest IMO requirements. The light and its 5-year battery are completely sealed providing a robust, corrosion-proof and tamper-proof unit for today's demanding market.

The AQ180's unique large dome allows light to be projected over a wider area, which dramatically increases visibility.

### TECHNICAL SPECIFICATIONS

Activation	Auto
Dimensions	160mm(h) x 80mm(w) x 80mm(d)
Output	2cd
Duration	Min 2hrs
Shelf Life	5 Years

0086/03  
MED 2002/84/EC, IMO MSC 81 (70)



# AQUA SPEC



SOLAS LIGHT RANGE



# AQ98

LIFEJACKET LIGHT

The smallest lifejacket light in the world, the Aquaspec AQ98 is a compact, tamper proof unit that combines both battery and light source in one. Its unique size and shape, combined with ease of attachment, has made the AQ98 the ideal light for fitment within an inflatable lifejacket. Used extensively in both leisure and commercial applications, AQ98 is also now used by The UK MOD.

## TECHNICAL SPECIFICATIONS

Activation	Auto On / Man Off
Dimensions	50mm(h) x 25mm(w) x 35mm(d)
Output	0.75cd
Duration	Min 8hrs
Shelf Life	5 Years



0086/99, MED 96/98/EC  
USCG 161.112/53/0 NATO No. 6230-99-607-3900

# AQ02U

LIFEJACKET LIGHT

Approved to the latest IMO testing standards, the Aquaspec AQ02 lifejacket lights offer a versatile product for the commercial and military markets.

The AQU02U (Universal) is designed to be used mainly on inflatable jackets. Its unique activation switch offers the user a choice of either manual or automatic operation.

## TECHNICAL SPECIFICATIONS

Activation	Mano On / Auto On / Man Off
Dimensions	65mm(h) x 30mm(w) x 45mm(d)
Output	0.75cd
Duration	Min 8hrs
Shelf Life	5 Years



0086/02  
MED 2002/75/EC, IMO MSC 81 (70)



# AQUA SPEC

Aquaspec Limited | Enterprise House | Ocean Village | Southampton | SO14 3XB

T. +44 (0) 23 8072 0800 | F. +44 (0) 23 8072 0801 | M. +44 (0) 7802 396 138

[www.aquaspec.co.uk](http://www.aquaspec.co.uk)